

# Accessories



**Series 151 & 151HD**  
Speedometer Pitot Tubing



**Series 157**  
LLDPE Vacuum Tubing



**Series 201**  
EPDM Wet Exhaust Flapper



**Series 305 to 309**  
Easy Oil Drain Kit



**Series 502, 503, & 507**  
Series 502 - 45° SAE Female Brass Swivel  
Series 503 - 45° SAE Female Brass Swivel  
Series 507 - Solid Brass Ferrule



**Series 720 - 721**  
Heavy-Duty Stainless Steel T-Bolt Clamps



**Series 747 - Black, 748 - White**  
Corrugated PVC Water Hose

## ACCESSORIES

### Series 151 & 151HD Speedometer Pitot Tubing



Black PVC tubing for connection between speedometer pickup and gauge. Series 151HD has a braided reinforcement for high-speed applications and maximum flexibility. Temperature range is -40°F to 150°F (-40°C to 66°C).

#### Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
151-0180	1/8"	TBD	3.175	.25	6.35	TBD
151-0400	4 mm	.157	4.0	.244	6.20	TBD
151-0400HD	4 mm	TBD	4.0	.327	8.3	0.22 (0.322)

#### Series 151 & 151HD

SKU	I.D.	Length	Color
151-0180	1/8"	1,200'	Black
151-0400	4 mm	1,200'	Black
151-0400HD	4 mm	300'	Black

## Series 157 LLDPE Vacuum Tubing



Semi-rigid tubing for use in fiberglass resin vacuum bagging operations. Good solvent and stress crack resistance materials comply with FDA specifications. Temperature range is -50°F to 150°F (-45°C to 66°C).

### Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
157-0120	3/8	.375	9.525	1/2"	12.7	TBD
157-0580	1/2"	.625	12.7		15.875	TBD

### Series 157

SKU	I.D.	Length	Color
157-0120	3/8	500'	Natural
157-0580	1/2"	.625	Natural

## Series 201 EPDM Wet Exhaust Flapper



EPDM compounded rubber exhaust flapper. Designed to prevent water from entering exhaust system. Weather and UV resistant.

Use with Series 721 Exhaust Flapper Clamps.

### Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
201-3000	3"	3.000	76.2	N/A	N/A	TBD
201-4000	4"	4.000	101.6	N/A	N/A	TBD

## Series 201

SKU	I.D.	Pgk. Qty.	Color
<b>201-3000</b>	<b>3"</b>	<b>1</b>	<b>Black</b>
<b>201-4000</b>	<b>4"</b>	<b>1</b>	<b>Black</b>

## Series 305 to 309 Easy Oil Drain Kit



It's quick and easy to drain engine oil without a pump. Simply push the hose through the transom drain plug hole or place anywhere below the oil pan. Assembly includes oil resistant hose with non-corrosive brass fittings. Available in sizes to fit most I/O engines.

- 305 1/2" – 20 Standard Chevy 1996 & prior
- 306 3/8" – 18 Mercruiser Inboard
- 307 3/4" – 16 Volvo Penta Inline
- 308 12 mm x 1.75 – Metric Chevy 1996 & later
- 309 14 mm x 1.5 – Metric Ford 302 & 351

## Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weight (lbs/ft)	Weight (kg/m)
<b>305-0380</b>	<b>3/8"</b>	<b>.375</b>	<b>9.5</b>	<b>.625"</b>	<b>15.875</b>	<b>TBD</b>	<b>TBD</b>
<b>306-0380</b>	<b>3/8"</b>	<b>.375</b>	<b>9.5</b>	<b>.625"</b>	<b>15.875</b>	<b>TBD</b>	<b>TBD</b>
<b>307-0380</b>	<b>3/8"</b>	<b>.375</b>	<b>9.5</b>	<b>.625"</b>	<b>15.875</b>	<b>TBD</b>	<b>TBD</b>
<b>308-0380</b>	<b>3/8"</b>	<b>.375</b>	<b>9.5</b>	<b>.625"</b>	<b>15.875</b>	<b>TBD</b>	<b>TBD</b>
<b>309-0380</b>	<b>3/8"</b>	<b>.375</b>	<b>9.5</b>	<b>.625"</b>	<b>15.875</b>	<b>TBD</b>	<b>TBD</b>

## Series 305 to 309

SKU	I.D.	Length	Color
<b>305-0380</b>	<b>3/8"</b>	<b>42"</b>	<b>Black</b>
<b>306-0380</b>	<b>3/8"</b>	<b>42"</b>	<b>Black</b>

SKU	I.D.	Length	Color
307-0380	3/8"	42"	Black
308-0380	3/8"	42"	Black
309-0380	3/8"	42"	Black

## Series 502, 503 & 507

**Series 502 – 45° SAE Female Brass Swivel**

**Series 503 – 45° SAE Female Brass Swivel**

**Series 507 – Solid Brass Ferrule**



Brass hose fittings, adapters, and ferrules meet SAE & JIC standards and specifications. Constructed of premium brass to resist corrosion in marine applications.

## Specifications

SKU	I.D.	IN	MM	Thread Size	Weight/lbs/ft (kg/m)
502-0140	1/4"	.250	6.4	SAE 7/16"-20	TBD
502-0560	5/16"	.312	7.9	SAE 1/2"-20	TBD
502-0380	3/8"	.375	9.5	SAE 5/8"-18	TBD
502-0120	1/2"	.500	12.7	SAE 3/4"-16	TBD
502-0580	5/8"	.625	15.9	SAE 7/8"-14	TBD
502-0340	3/4"	.750	19.1	SAE 1-1/16"-12	TBD
503-0340	3/4"	.750	19.1	SAE 1-1/16"-12	TBD
503-1000	1/4"	1.000	25.4	SAE 1-1/16"-12	TBD
507-0550	1/4"	.550			TBD
507-0560	1/4"	.560			TBD
507-0575	1/4"	.575			TBD
507-0625	1/4"	.625			TBD

SKU	I.D.	IN	MM	Thread Size	Weightlbs/ft (kg/m)
507-0650	1/4"	.650			TBD
507-0675	1/4"	.675			TBD
507-0700	3/8"	.700			TBD
507-0775	3/8"	.775			TBD
507-0825	3/8"	.825			TBD
507-0850	1/2"	.850			TBD
507-0925	1/2"	.925			TBD
507-1000	5/8"	1.000			TBD
507-1050	5/8"	1.050			TBD
507-1225	3/4"	1.225			TBD
507-1437	1"	1.437			TBD

### Series 502, 503 & 507

SKU	I.D.	Length	Color	Pkg Qty.
502-0140	1/4"		Brass	1
502-0560	5/16"		Brass	1
502-0380	3/8"		Brass	1
502-0120	1/2"		Brass	1
502-0580	5/8"		Brass	1
502-0340	3/4"		Brass	1
503-0340	3/4"		Brass	1
503-1000	1/4"		Brass	1
507-0550	1/4"	1"	Brass	1
507-0560	1/4"	1"	Brass	1
507-0575	1/4"	1"	Brass	1

SKU	I.D.	Length	Color	Pkg Qty.
507-0625	1/4"	1"	Brass	1
507-0650	1/4"	1"	Brass	1
507-0675	1/4"	1"	Brass	1
507-0700	3/8"	1"	Brass	1
507-0775	3/8"	1"	Brass	1
507-0825	3/8"	1"	Brass	1
507-0850	1/2"	1"	Brass	1
507-0925	1/2"	1"	Brass	1
507-1000	5/8"	1"	Brass	1
507-1050	5/8"	1"	Brass	1
507-1225	3/4"	1"	Brass	1
507-1437	1"	1"	Brass	1

## Series 720 – 721 Heavy-Duty Stainless Steel T-Bolt Clamps



Excellent for all exhaust and many other marine applications. 360° clamping surface assures proper retention. Constructed of 316 stainless steel with nylon insert lock nut. Maximum clamp adjustment with extra long T-bolt.

Only **Heavy-Duty T-bolt clamps** should be used on elbows, hump hoses and reducers. ABYC recommends double clamping each connection with Series 720 Heavy-Duty T-bolt clamps for maximum safety, per ABYC Section 1.7.1.10. Add -**SS** to end of a hose part number to order for package of 4 stainless steel T-bolt clamps.

## Specifications

SKU	I.D.	RANGE O.D. (in)	Weight (lbs/ft)
720-1000	1"	1.36" to 1.50"	TBD
720-1120	1-1/2"	1.87" to 2.12"	TBD
720-1340	1-3/4"	2.03" to 2.34"	TBD
720-2000	2"	2.23" to 2.54"	TBD
720-2120	2-1/2"	2.78" to 3.09"	TBD
720-3000	3"	3.30" to 3.95"	TBD
720-3120	3-1/2"	3.50" to 4.15"	TBD
720-4000	4"	4.13" to 4.78"	TBD
720-4120	4-1/2"	4.75" to 5.40"	TBD
720-5000	5"	5.30" to 5.95"	TBD
720-5120	5-1/2"	5.90" to 6.55"	TBD
720-6000	6"	6.35" to 7.00"	TBD
720-8000	8"	8.40" to 9.05"	TBD
720-10000	10"	10.50" to 11.15"	TBD
720-12000	12"	12.50" to 13.15"	TBD
720-14000	14"	14.60" to 15.25"	TBD
720-16000	16"	16.20" to 16.85"	TBD
720-20000	20"	20.13" to 20.78"	TBD
721-3000	3"	3" Exhaust Flapper	TBD
721-4000	4"	3" Exhaust Flapper	TBD

## Series 720 – 721

SKU	I.D.	Ea.	Color
720-1000	1"	1	Stainless Steel



SKU	I.D.	Ea.	Color
720-1120	1-1/2"	1	Stainless Steel
720-1340	1-3/4"	1	Stainless Steel
720-2000	2"	1	Stainless Steel
720-2120	2-1/2"	1	Stainless Steel
720-3000	3"	1	Stainless Steel
720-3120	3-1/2"	1	Stainless Steel
720-4000	4"	1	Stainless Steel
720-4120	4-1/2"	1	Stainless Steel
720-5000	5"	1	Stainless Steel
720-5120	5-1/2"	1	Stainless Steel
720-6000	6"	1	Stainless Steel
720-8000	8"	1	Stainless Steel
720-10000	10"	1	Stainless Steel
720-12000	12"	1	Stainless Steel
720-14000	14"	1	Stainless Steel
720-16000	16"	1	Stainless Steel
720-20000	20"	1	Stainless Steel
721-3000	3"	1	Stainless Steel
721-4000	4"	1	Stainless Steel

## Series 747-Black, 748-White Outboard Rigging Flange



Premium quality, crush resistant proprietary PE blend construction provides excellent flexing and abrasion protection. Material is resistant to bilge acids, fuel solutions, and ultra violet rays. For all bracket mounted outboard motors. Is formulated for maximum resistance to UV and ozone. Temperature range is -40 F° 160 F° (-40 C° to +71 C°)

### Specifications

SKU	I.D.	IN	Weight (lbs/ft)	Color
<b>747-2000</b>	<b>2"</b>	<b>2.500</b>	<b>TBD</b>	<b>Black</b>
<b>747-2120</b>	<b>2-1/2"</b>	<b>3.000</b>	<b>TBD</b>	<b>Black</b>
<b>747-3000</b>	<b>3"</b>	<b>3.500</b>	<b>TBD</b>	<b>Black</b>
<b>748-2000</b>	<b>2"</b>	<b>2.500</b>	<b>TBD</b>	<b>White</b>

### Series 747-Black, 748-White

SKU	I.D.	IN	MM	Weight (kg/m)	Pkg Qty. (ft)
<b>747-2000</b>	<b>2"</b>	<b>2.500</b>	<b>63.5</b>	<b>TBD</b>	<b>1 ea</b>
<b>747-2120</b>	<b>2-1/2"</b>	<b>3.000</b>	<b>76.2</b>	<b>TBD</b>	<b>1 ea</b>
<b>747-3000</b>	<b>3"</b>	<b>3.500</b>	<b>88.9</b>	<b>TBD</b>	<b>1 ea</b>
<b>748-2000</b>	<b>2"</b>	<b>2.500</b>	<b>63.5</b>	<b>TBD</b>	<b>1 ea</b>