

Wet Exhaust Systems



Series 200
Softwall (Non-wire)



Series 250
Hardwall (Single Wire)



Series 252
Corrugated (Double Wire)

WET EXHAUST SYSTEMS

Series 200 Softwall (Non-Wire)



Our premium softwall wet exhaust marine hose is certified for wet exhaust service. Recommended for short, straight connections. Heavy wall construction with multiple plies of nylon spiral cord prevents shock, wall collapse, panting and vibration. Also resists engine exhaust, high temperatures and ozone. Color coded blue stripe. Meets or exceeds SAE J2006 R1 standard, and has double the ozone resistance required by the [SAE J2006 standard](#).

- Formulated for maximum resistance to heat, weather, UV and ozone resistance.
- Temperature range is -20°F to 220°F (-29°C to 100°C).

ABYC recommends double clamping each connection with series [720 Heavy-Duty T-Bolt clamps](#) for maximum safety, per [ABYC Section 1.7.1.10](#).

Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
200-1120	1-1/2"	1.500	38.1	1.870"	1.870	0.56 (0.830)
200-1126	1-1/2"	1.500	38.1	1.870"	1.870	0.56 (0.830)
200-1580	1-5/8"	1.625	41.5	2.004"	2.004	0.60 (0.896)
200-1586	1-5/8"	1.625	41.5	2.004"	2.004	0.60 (0.896)
200-1340	1-3/4"	1.775	45.1	2.146"	2.146	0.65 (0.964)
200-1346	1-3/4"	1.775	45.1	2.146"	2.146	0.65 (0.964)
200-1780	1-7/8"	1.875	47.6	2.307"	2.307	0.82 (1.217)
200-1786	1-7/8"	1.875	47.6	2.307"	2.307	0.82 (1.217)
200-2000	2"	2.000	50.8	2.496"	2.496	1.01 (1.510)
200-2006	2"	2.000	50.8	2.496"	2.496	1.01 (1.510)

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
200-2180	2-1/8"	2.125	54.0	2.635"	2.635	1.08 (1.610)
200-2186	2-1/8"	2.125	54.0	2.635"	2.635	1.08 (1.610)
200-2140	2-1/4"	2.250	57.2	2.750"	2.750	1.18 (1.760)
200-2146	2-1/4"	2.250	57.2	2.750"	2.750	1.18 (1.760)
200-2380	2-3/8"	2.875	60.3	2.875"	2.875	1.19 (1.770)
200-2386	2-3/8"	2.375	60.3	2.875"	2.875	1.19 (1.770)
200-2120	2-1/2"	2.500	63.5	2.988"	2.988	1.21 (1.795)
200-2126	2-1/2"	2.500	63.5	2.988"	2.988	1.21 (1.795)
200-2580	2-5/8"	2.625	66.7	3.125"	3.125	1.34 (1.990)
200-2586	2-5/8"	2.625	66.7	3.125"	3.125	1.34 (1.990)
200-2340	2-3/4"	2.750	69.9	3.250"	3.250	1.38 (2.050)
200-2346	2-3/4"	2.750	69.9	3.250"	3.250	1.38 (2.050)
200-2780	2-7/8"	2.875	73.0	3.4375"	3.438	1.40 (2.080)
200-2786	2-7/8"	2.875	73.0	3.4375"	3.438	1.40 (2.080)
200-3000	3"	3.000	76.2	3.488"	3.488	1.43 (2.123)
200-3006	3"	3.000	76.2	3.488"	3.488	1.43 (2.123)
200-3180	3-1/8"	3.125	79.4	3.688"	3.688	1.47 (2.190)
200-3186	3-1/8"	3.125	79.4	3.688"	3.688	1.47 (2.190)
200-3120	3-1/2"	3.500	89.9	3.996	3.996	1.54 (2.295)
200-3126	3-1/2"	3.500	89.9	3.996	3.996	1.54 (2.295)
200-3340	3-3/4"	3.750	95.4	4.275"	4.275	1.89 (2.998)
200-4000	4"	4.000	101.6	4.551"	4.551	2.14 (3.181)
200-4006	4"	4.000	101.6	4.551"	4.551	2.14 (3.181)

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
200-4180	4-1/8"	4.125	104.8	4.625"	4.625	2.36 (3.510)
200-4120	4-1/2"	4.500	114.3	5.114"	5.114	2.69 (4.008)
200-5000	5"	5.000	127	5.614"	5.614	2.97 (4.424)
200-5120	5-1/2"	5.500	139.7	6.1875"	6.188	3.56 (5.300)
200-6000	6"	6.000	152.4	6.677"	6.677	3.63 (5.409)
200-6580	6-5/8"	6.625	168.3	7.4375"	7.438	5.26 (7.830)
200-8000	8"	8.000	203.2	8.750"	8.750	6.10 (9.080)
200-8120	8-1/2"	8.500	215.9	9.250"	9.250	6.40 (9.520)
200-10000	10"	10.000	254.0	10.724"	10.724	6.62 (9.848)
200-12000	12"	12.000	304.8	13.000"	13.000	8.20 (12.200)

SKU	I.D.	Length	Color
200-1120	1-1/2"	12.5'	Black
200-1126	1-1/2"	50'	Black
200-1580	1-5/8"	12.5'	Black
200-1586	1-5/8"	50'	Black
200-1340	1-3/4"	12.5'	Black
200-1346	1-3/4"	50'	Black
200-1780	1-7/8"	12.5'	Black
200-1786	1-7/8"	50'	Black
200-2000	2"	12.5'	Black
200-2006	2"	50'	Black
200-2180	2-1/8"	12.5'	Black

SKU	I.D.	Length	Color
200-2186	2-1/8"	50'	Black
200-2140	2-1/4"	12.5'	Black
200-2146	2-1/4"	50'	Black
200-2380	2-3/8"	12.5'	Black
200-2386	2-3/8"	50'	Black
200-2120	2-1/2"	12.5'	Black
200-2126	2-1/2"	50'	Black
200-2580	2-5/8"	12.5'	Black
200-2586	2-5/8"	50'	Black
200-2340	2-3/4"	12.5'	Black
200-2346	2-3/4"	50'	Black
200-2780	2-7/8"	12.5'	Black
200-2786	2-7/8"	50'	Black
200-3000	3"	12.5'	Black
200-3006	3"	50'	Black
200-3180	3-1/8"	12.5'	Black
200-3186	3-1/8"	50'	Black
200-3120	3-1/2"	12.5'	Black
200-3126	3-1/2"	50'	Black
200-3340	3-3/4"	12.5'	Black
200-4000	4"	12.5'	Black
200-4006	4"	50'	Black
200-4180	4-1/8"	12.5'	Black

SKU	I.D.	Length	Color
200-4120	4-1/2"	12.5'	Black
200-5000	5"	12.5'	Black
200-5120	5-1/2"	12.5'	Black
200-6000	6"	12.5'	Black
200-6580	6-5/8"	12.5'	Black
200-8000	8"	12.5'	Black
200-8120	8-1/2"	12.5'	Black
200-10000	10"	12.5'	Black
200-12000	12"	12.5'	Black

WET EXHAUST SYSTEMS

Series 250 Hardwall (Single Wire)



Our premium hardwall wet exhaust marine hose is certified for wet exhaust service. Offers the same features as our premium softwall exhaust hose. In addition, wire reinforcement provides additional strength for longer connections with excellent flexibility. Heavy-duty wall construction with multiple plies of nylon spiral cord prevents shock, wall collapse, panting and vibration. Resists engine exhaust, high temperatures and ozone. Recommended for runs longer than four times the inside diameter of the hose. Color coded with a blue stripe. Meets or exceeds SAE J2006 R2 standard, and has double the ozone resistance required by the [SAE J2006 standard](#).

- Formulated for maximum resistance to heat, weather, UV and ozone resistance.
- Temperature range is -20°F to 220°F (-29°C to 104°C).

ABYC recommends double clamping each connection with series [720 Heavy-Duty T-Bolt clamps](#) for maximum safety, per [ABYC Section 1.7.1.10](#).

Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
250-1120	1-1/2"	1.500	38.1	1.866"	47.4	0.63 (0.931)
250-1126	1-1/2"	1.500	38.1	1.866"	47.4	0.63 (0.931)
250-1580	1-5/8"	1.625	41.5	2.001"	50.8	0.69 (1.028)
250-1586	1-5/8"	1.625	41.5	2.001"	50.8	0.69 (1.028)
250-1340	1-3/4"	1.750	45.1	2.142"	54.4	0.74 (1.107)
250-1346	1-3/4"	1.750	45.1	2.142"	54.4	0.74 (1.107)
250-1780	1-7/8"	1.875	47.6	2.300"	58.4	0.93 (1.380)
250-1786	1-7/8"	1.875	47.6	2.300"	58.4	0.93 (1.380)
250-2000	2"	2.000	50.8	2.402"	61.0	0.94 (1.403)
250-2006	2"	2.000	50.8	2.402"	61.0	0.94 (1.403)
250-2380	2-3/8"	2.375	60.8	2.765"	70.2	1.05 (1.565)
250-2386	2-3/8"	2.375	60.8	2.765"	70.2	1.05 (1.565)
250-2120	2-1/2"	2.500	63.5	2.873"	73.0	1.10 (1.630)
250-2126	2-1/2"	2.500	63.5	2.873"	73.0	1.10 (1.630)
250-2340	2-3/4"	2.750	70.1	3.306"	84.0	1.75 (2.605)
250-2346	2-3/4"	2.750	70.1	3.306"	84.0	1.75 (2.605)
250-3000	3"	3.000	76.2	3.546"	90.1	1.89 (2.818)
250-3006	3"	3.000	76.2	3.546"	90.1	1.89 (2.818)
250-3120	3-1/2"	3.500	89.9	4.086"	103.8	2.21 (3.283)
250-3126	3-1/2"	3.500	89.9	4.086"	103.8	2.21 (3.283)

SKU	I.D.	IN	MM	O.D.	MM	Weightlbs/ft (kg/m)
250-4000	4"	4.000	101.6	4.630"	117.6	2.96 (4.401)
250-4006	4"	4.000	101.6	4.630"	117.6	2.96 (4.401)
250-4120	4-1/2"	4.500	114.3	5.168"	131.3	3.47 (5.168)
250-4126	4-1/2"	4.500	114.3	5.168"	131.3	3.47 (5.168)
250-5000	5"	5.000	127	5.488"	139.4	4.02 (5.501)
250-6000	6"	6.000	152.4	6.750"	171.4	5.58 (8.311)
250-8000	8"	8.000	203.4	8.875"	222.5	7.75 (11.538)

SKU	I.D.	Length	Color
250-1120	1-1/2"	12.5'	Black
250-1126	1-1/2"	50'	Black
250-1580	1-5/8"	12.5'	Black
250-1586	1-5/8"	50'	Black
250-1340	1-3/4"	12.5'	Black
250-1346	1-3/4"	50'	Black
250-1780	1-7/8"	12.5'	Black
250-1786	1-7/8"	50'	Black
250-2000	2"	12.5'	Black
250-2006	2"	50'	Black
250-2380	2-3/8"	12.5'	Black
250-2386	2-3/8"	50'	Black
250-2120	2-1/2"	12.5'	Black
250-2126	2-1/2"	50'	Black

SKU	I.D.	Length	Color
250-2340	2-3/4"	12.5'	Black
250-2346	2-3/4"	50'	Black
250-3000	3"	12.5'	Black
250-3006	3"	50'	Black
250-3120	3-1/2"	12.5'	Black
250-3126	3-1/2"	50'	Black
250-4000	4"	12.5'	Black
250-4006	4"	50'	Black
250-4120	4-1/2"	12.5'	Black
250-4126	4-1/2"	50'	Black
250-5000	5"	12.5'	Black
250-6000	6"	12.5'	Black
250-8000	8"	12.5'	Black

WET EXHAUST SYSTEMS

Series 252 Corrugated (Double Wire)



Our premium corrugated wet exhaust marine hose is certified for wet exhaust service. Offers the same features as our premium softwall (Series 200) and hardwall (Series 250) exhaust hose. In addition, the corrugated construction with double wire helix embedded between two rayon spiral cords provides excellent strength and flexibility. Color coded with a blue stripe. Meets or exceeds SAE J2006 R2 standard, and has double the ozone resistance required by the [SAE J2006 standard](#).



- Formulated for maximum resistance to heat, weather, UV and ozone resistance.
- Temperature range is -20°F 220°F (-29°C to 104°C).

ABYC recommends double clamping each connection with series [720 Heavy-Duty T-Bolt clamps](#) for maximum safety, per [ABYC Section 1.7.1.10](#).

Specifications

SKU	I.D.	IN	MM	O.D.	MM	Weight (lbs/ft)
252-4000	4"	4.000	101.6	4.630"	61.0	2.96
252-4120	4-1/2"	4.500	114.3	5.168"	58.4	3.47
252-5000	5"	5.000	127	5.488"	54.4	
252-6000	6"	6.000	152.4	6.750"	50.8	
252-8000	8"	8.000	203.4	8.875"	47.4	
252-3120	3-1/2"	3.500	89.9	4.086"	68.3	
252-2340	2-3/4"	2.750	70.1	3.306"	70.2	
252-3000	3"	3.000	76.2	3.546"	73.0	1.89
252-2120	2-1/2"	2.250	63.5	2.873"	84.0	1.10
252-2000	2"	2.000	50.8	2.402"	90.1	0.94
252-2140	2-1/4"	2.250	57.2	2.688"	103.8	0.98
252-2380	2-3/8"	2.375	60.8	2.765"	117.6	
252-1120	1-1/2"	1.500	38.1	1.866"	131.3	0.63
252-1580	1-5/8"	1.625	41.5	2.001"	139.4	
252-1340	1-3/4"	1.750	45.1	2.142"	171.4	
252-1780	1-7/8"	1.875	47.6	2.300"	222.5	0.93

SKU	I.D.	Length	Color
252-4000	4"	50'	Black



SKU	I.D.	Length	Color
252-4120	4-1/2"	50'	Black
252-5000	5"	12.5'	Black
252-6000	6"	12.5'	Black
252-8000	8"	12.5'	Black
252-3120	3-1/2"	50'	Black
252-2340	2-3/4"	50'	Black
252-3000	3"	50'	Black
252-2120	2-1/2"	50'	Black
252-2000	2"	50'	Black
252-2140	2-1/4"	50'	Black
252-2380	2-3/8"	50'	Black
252-1120	1-1/2"	50'	Black
252-1580	1-5/8"	50'	Black
252-1340	1-3/4"	50'	Black
252-1780	1-7/8"	50'	Black